

Hot water high-pressure
cleaners

Sundek 5Y LP

WATER COOLING
(three phase models)



Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection and water cooling (three phase models)
- Three ceramic coated pistons, brass linear pump head (1 ph), full ceramic pistons (3 ph), brass linear pump head with built-in by-pass valve
- Vertical burner with high thermal efficiency steel coil.
- Suction and delivery S/S valves. • Safety valve • Temperature regulation gauge • Glycerine pressure gauge. • Automatic Stop System late shut down protection 24V. • Adjustable detergent delivery with built-in tank for indirect suction. • Auxiliary motor for burner air-cooling • Two ways fuel pump • Low fuel lamp • Ergonomic handles and impact resistant covers • Accessory holder
- Power cable (m 5).

Standard equipment:



Optional:

- Hose-reel with brake code 6.608.0077
- Antiscale LC-PRECAL (pcs. 4 x 5 lt.) code 3.697.0044

Sundek 5Y 1311 LP

Sundek 5Y 1515 LP

Sundek 5Y 2015 LP

	Sundek 5Y 1311 LP	Sundek 5Y 1515 LP	Sundek 5Y 2015 LP
Code	8.621.2948	8.621.2942	8.621.2943
Operat. pressure bar	30 ÷ 110	30 ÷ 150	30 ÷ 200
Operat. pressure psi	1595	2175	2900
Delivery rate l/h	330 ÷ 660	450 ÷ 900	450 ÷ 900
Temp. max	110°C	110°C	110°C
Power ass. W	3000	5500	7300
RPM	1450	1450	1450
Voltage	230 V~50 Hz	400 V~50 Hz	400 V~50 Hz